



Link® Cat's Eye® Tire Pressure Maintenance System - Ordering Guide -

Does the customer have single axle or tandem axle with dual tires on the truck/tractor/trailer?

Cat's Eye 2 pack will do one axle, 4 unit box can do 2 axles and is slightly less expensive.

Single / Tandem

How many axles with dual tires need the Cat's Eye Tire Pressure Monitors?

times 2 = Cat's Eyes required.

Does the customer have super single tires? How many super single tires need Cat's Eyes?

Available with 12" rubber and stainless hoses, only - ONE per tire.

Yes / No

#

To what pressure (psi) does the customer inflate tires?

Does the customer prefer rubber hoses or stainless steel braided hoses?

The stainless hoses are preferred on chrome or polished wheels for appearance. They may provide protection from the sun, and increase hose life in extreme temperatures, but the main advantage is appearance.

Rubber / Stainless Steel Braid

What hose length does the customer want?

22.5 and 24.5 tires normally use the 16" hose.

19.5 tires normally use the 14" hose.

17.5 tires normally use the 12" hose.

16"	<input type="text"/>
14"	<input type="text"/>
12"	<input type="text"/>
SSingle	<input type="text"/>

Part Number Chart

2 Packs		60psi	65psi	70psi	75psi	80psi	85psi	90psi	95psi	100psi	105psi	110psi	115psi	120psi	125psi
CE with 12" Rubber Hoses	Dual Tire	6060AF00	6065AF00	6070AF00	6075AF00	6080AF00	6085AF00	6090AF00	6095AF00	6100AF00	6105AF00	6110AF00	6115AF00	6120AF00	6125AF00
CE with 12" Stainless Hoses	Dual Tire	6060AH00	6065AH00	6070AH00	6075AH00	6080AH00	6085AH00	6090AH00	6095AH00	6100AH00	6105AH00	6110AH00	6115AH00	6120AH00	6125AH00
CE with 12" Rubber Hoses	Super Single	6060AC00	6065AC00	6070AC00	6075AC00	6080AC00	6085AC00	6090AC00	6095AC00	6100AC00	6105AC00	6110AC00	6115AC00	6120AC00	6125AC00
CE with 12" Stainless Hoses	Super Single	6060AJ00	6065AJ00	6070AJ00	6075AJ00	6080AJ00	6085AJ00	6090AJ00	6095AJ00	6100AJ00	6105AJ00	6110AJ00	6115AJ00	6120AJ00	6125AJ00
CE with 14" Rubber Hoses	Dual Tire	6060AE00	6065AE00	6070AE00	6075AE00	6080AE00	6085AE00	6090AE00	6095AE00	6100AE00	6105AE00	6110AE00	6115AE00	6120AE00	6125AE00
CE with 14" Stainless Hoses	Dual Tire	6060AG00	6065AG00	6070AG00	6075AG00	6080AG00	6085AG00	6090AG00	6095AG00	6100AG00	6105AG00	6110AG00	6115AG00	6120AG00	6125AG00
CE with 16" Rubber Hoses	Dual Tire	6060AA00	6065AA00	6070AA00	6075AA00	6080AA00	6085AA00	6090AA00	6095AA00	6100AA00	6105AA00	6110AA00	6115AA00	6120AA00	6125AA00
CE with 16" Stainless Hoses	Dual Tire	6060AB00	6065AB00	6070AB00	6075AB00	6080AB00	6085AB00	6090AB00	6095AB00	6100AB00	6105AB00	6110AB00	6115AB00	6120AB00	6125AB00
4 Unit Box		60psi	65psi	70psi	75psi	80psi	85psi	90psi	95psi	100psi	105psi	110psi	115psi	120psi	125psi
CE with 12" Rubber Hoses	Dual Tire	6060BF00	6065BF00	6070BF00	6075BF00	6080BF00	6085BF00	6090BF00	6095BF00	6100BF00	6105BF00	6110BF00	6115BF00	6120BF00	6125BF00
CE with 12" Stainless Hoses	Dual Tire	6060BH00	6065BH00	6070BH00	6075BH00	6080BH00	6085BH00	6090BH00	6095BH00	6100BH00	6105BH00	6110BH00	6115BH00	6120BH00	6125BH00
CE with 12" Rubber Hoses	Super Single	6060BC00	6065BC00	6070BC00	6075BC00	6080BC00	6085BC00	6090BC00	6095BC00	6100BC00	6105BC00	6110BC00	6115BC00	6120BC00	6125BC00
CE with 12" Stainless Hoses	Super Single	6060BJ00	6065BJ00	6070BJ00	6075BJ00	6080BJ00	6085BJ00	6090BJ00	6095BJ00	6100BJ00	6105BJ00	6110BJ00	6115BJ00	6120BJ00	6125BJ00
CE with 14" Rubber Hoses	Dual Tire	6060BE00	6065BE00	6070BE00	6075BE00	6080BE00	6085BE00	6090BE00	6095BE00	6100BE00	6105BE00	6110BE00	6115BE00	6120BE00	6125BE00
CE with 14" Stainless Hoses	Dual Tire	6060BG00	6065BG00	6070BG00	6075BG00	6080BG00	6085BG00	6090BG00	6095BG00	6100BG00	6105BG00	6110BG00	6115BG00	6120BG00	6125BG00
CE with 16" Rubber Hoses	Dual Tire	6060BA00	6065BA00	6070BA00	6075BA00	6080BA00	6085BA00	6090BA00	6095BA00	6100BA00	6105BA00	6110BA00	6115BA00	6120BA00	6125BA00
CE with 16" Stainless Hoses	Dual Tire	6060BB00	6065BB00	6070BB00	6075BB00	6080BB00	6085BB00	6090BB00	6095BB00	6100BB00	6105BB00	6110BB00	6115BB00	6120BB00	6125BB00