


INSTALLATION INSTRUCTIONS



IHC93-B (2476-B000)



The **CABMATE MODEL IHC93-B** fits most International 9300, 9400, 9500 (Severe Service) Series Conventionals, also fits International 9200 Series Conventionals with Cummins, and Cat engines before January 1997. It replaces the original rear two-piece cab support, Navistar Part Nos. 432364C1 and 598073C1.

Link mfg. Ltd.
223 15th St. N.E.
Sioux Center, IA USA
51250-2120

(712) 722-4874
Fax (712) 722-4876

**QUESTIONS?
CALL CUSTOMER
SERVICE
1-800-222-6283**

UNIT WEIGHT : 33.1 LB.

NET WEIGHT ADDED: 21.3 LB.




CABMATE[®] MODEL IHC93-B

Review the Parts List on page 3 to become familiar with the different components of the CABMATE.

IMPORTANT: Due to many chassis variables caused by installation of special equipment or options, the fit of the IHC93-B CABMATE may be affected and should be evaluated before beginning installation.


IMPORTANT: Installation of the CABMATE system will allow the cab to move freely. Before starting installation, check clearances between the cab and any objects the cab may contact when it moves (1 1/2 inches of clearance should be sufficient). The clearance of components that are affected by cab movement, such as exhaust and radiator systems, must also be evaluated.

- A. Remove the eight mount bolts from the top of the stock mount. Securely prop up the cab and remove all stock mount parts. **NOTE:** Save all stock mount bolts for later use (Fig. 1).
- B. The IHC93-B CABMATE has two Height Control Valve mounting positions, one on either side of the unit. Select the position that does not cause interference with existing components and mount the Height Control Valve in one of the positions shown in Fig.2. Connect the Airline from the Height Control Valve to the Air Spring. (**NOTE:** the Male Elbow in the Air Spring may have to be turned.)
- C. Loosely fasten the Unit Bottom to the cross member using the four original bottom mount bolts. (Fig. 2)
- D. Slowly lower the cab until it touches the top of the CABMATE. Fasten the Unit Top to the cab frame using the two 1/2" bolts supplied by Link Mfg., (item no's 11, 18, and 21 on the parts list) and four of the original top mount bolts. **SECURELY TIGHTEN ALL FASTENERS.** Lower the cab completely.
- E. See page 2 for plumbing instructions and height adjustments.
- F. **IMPORTANT:** After plumbing and height control adjustments are completed, temporarily adjust the CABMATE to its maximum upward position. There must be a 1/4" to 3/8 gap between the cab and the hood. Adjust the hood hinge forward as necessary (Fig. 3).



PLUMBING INSTRUCTIONS

WARNING: FOR SAFTY PURPOSES THE CABMATE MUST BE SUPPLIED FROM A PRESSURE PROTECTED CIRCUIT. IN THE EVENT OF AN AIR LEAK IN THE CAB SUSPENSION, FAILURE TO PROVIDE A PRESSURE PROTECTED CIRCUIT MAY CAUSE LOSS OF AIR PRESSURE TO VITAL SYSTEMS ON THE VEHICLE.




WARNING: LOSS OR APPLICATION OF AIR PRESSURE TO CABMATE WILL CAUSE SUDDEN MOVEMENT OF THE CAB. PRIOR TO INSTALLING OR PERFORMING MAINTENANCE, BLOCK UP THE CABMATE TO PREVENT THE POSSIBILITY OF INJURY.

WARNING: CONNECT THE CABMATE DIRECTLY TO THE MAIN AIR TANK. YOU WILL NEED AN AIR PRESSURE PROTECTION VALVE IN THE LINE. (INCLUDED IN THE PRESSUREPROTECTION KIT. LINK MFG. PART NO. 1350-0000). DO NOT USE AN AIR PRESSURE REGULATOR!

- A. With the tank at 0 p.s.i., remove the existing plug or fitting from the desired port.
- B. Apply joint compound to the fittings and install the pressure protection kit. **DO NOT USE TEFLON TAPE.** Be sure that the arrows on the valve are pointing in the direction of air flow and the vent hole is pointed down. **NOTE:** Additional fittings/reducers may be required to attach the hex nipple to the main air tank.
- C. Run the 1/4" airline from the shut-off valve to the CABMATE. Be sure that the airline has enough clearance so that there are no pinch points that may restrict or cut the airline. Secure the airline using the cable ties supplied by Link Mfg.
- D. Tighten all plumbing fittings. Then, with the system at operating pressure (90 to 110 p.s.i.), open the Manual Shut-off Valve to supply air to the CABMATE. Check the system for air leaks.
- E. Check for proper operation of the height control valve. Disconnect the valve linkage from the lever. Push the lever down 45°, air should flow into the air spring(s). Return the lever to the neutral position. Push the lever up 45°, air should exhaust from the air spring(s). Return the lever to the neutral position; no air should flow. Reconnect the valve linkage to the lever.

HEIGHT ADJUSTMENTS

Measure the design height of the air spring (s). The height should be 5 5/8 inches ± 1/16. To change the height, disconnect one




end of the valve linkage and adjust accordingly. Tighten the lock nuts on the valve linkage.

MAINTENANCE

CABMATES need no lubrication and little maintenance. The following components should be checked at the time the truck is being serviced. However, immediate corrective action should be taken if a serious malfunction occurs.

COMPONENT	POSSIBLE PROBLEM	CORRECTIVE ACTION	TORQUE
Airlines	Air leaks	Replace airline	Compression Nut Hand Tight + 1 Turn
Fittings	Air leaks	Remove fitting and apply fresh joint compound. Reinstall fitting, but Do Not Overtighten. Do not use teflon tape.	Threaded into: Metal Plastic 15 Hand Tight Ft. Lbs. + 1 Turn
Air Springs	A. Improper height B. Air leakage	A. Adjust valve linkage to maintain proper air spring height. B. Replace air spring.	Size Metal Plastic 3/8 25 Ft. Lbs 04 Ft. Lbs 1/2 28 Ft. Lbs 10 Ft. Lbs 3/4 30 Ft. Lbs 10 Ft. Lbs
Height Control Valve	Air spring(s) will not inflate when wheight is added to the cab; OR Air spring(s) will not deflate when wheight is removed from the cab.	A. Inspect valve to insure drive bearing notch is located on "SUSP" port side of valve. If not, loosen lever screw (but do not remove completely) and pull lever loose from drive bearing, rotate drive bearing until the bearing notch is in the correct position and resecure lever by tightening lever screw. B. Replace Valve	1/4 Mount Fasteners 10 Ft. Lbs. Bearing Screw 40-50 InLbs.
Shock Absorber	Insufficient dampening effect	Replace shocks	45 Ft. Lbs.
Lateral Control Rod	A. Loose nuts on lateral control rod bolts B. Worn bushings.	A. Tighten securely to clamp the inner sleeve. B. Replace lateral control rod.	40 Ft. Lbs.

IMPORTANT: Periodically check the tightness of all fasteners.



CABMATE® MODEL IHC93-B PARTS LIST

ITEM	PART NO.	DESCRIPTION	QTY	ITEM	PART NO.	DESCRIPTION	QTY
1	1101-0040	SPRING-AIR	1	16	1475-2400	3/4 UNF HEX JAM NUT	1
2	1201-1043	SHOCK ABSORBER	2	17	1476-0800	1/4 UNC HEX CTR LOCK NUT (GR B)	4
3	1302-0090	AIRLINE-NYLON, .250 O.D., BULK	1.1 ft	18	1476-1000	5/16 UNC HEX CTR LOCK NUT (GR B)	1
4	1302-1038	.25 TUBE SUPPORT	1	19	1476-1600	1/2 UNC HEX CTR LOCK NUT (GR B)	2
5	1302-1105	ELBOW, 1/4 TB 1/8 M-NPT	1	20	1477-1400	7/16 UNF HEX CTR LOCK NUT (GR B)	4
6	1302-5499	ELBOW, 1/4 TB 1/4 PTC, PUSH-IN DOT	1	21	1477-1601	1/2 UNF HEX TOP LOCK NUT (GR C)	2
-	1350-0000	KIT-PROTECTION, PRESSURE	1	22	1487-1600	1/2 TYPE A PLAIN WASHER	2
7	1350-0101	ASSEMBLY-HEIGHT CONTROL VALVE	1	23	1500-0070	BUMPER-JOUNCE, 1.75	1
8	1401-0806	1/4 X 3/4 UNC HEX CAP SCR (GR 5)	2	24	1500-0252	LINKAGE-VALVE, HEIGHT CONTROL (4.75)	1
9	1401-0814	1/4 X 1 3/4 UNC HEX CAP SCR (GR 5)	2	25	2476-1000	UNIT TOP	1
10	1401-1012	5/16 X 1 1/2 UNC HEX CAP SCR (GR 5)	1	26	2476-1010	TOP VALVE MOUNT	1
11	1401-1610	1/2 X 1 1/4 UNC HEX CAP SCR (GR 5)	2	27	2476-2100	UNIT BOTTOM	1
12	1403-1426	7/16 X 3 1/4 UNF HEX CAP SCR (GR 5)	1	28	2476-2208	MOUNT-VALVE	1
13	1403-1428	7/16 X 3 1/2 UNF HEX CAP SCR (GR 5)	2	29	2991-0026	KIT-PIVOT BALL	2
14	1403-1430	7/16 X 3 3/4 UNF HEX CAP SCR (GR 5)	1	30	2993-2006	LATERAL CONTROL ROD	1
15	1404-1624	1/2 X 3 UNF HEX CAP SCR (GR 8)	2	-	3476-1001	KIT-DOCUMENT, IHC93-B	1