

# Link | Ramps

## ORDERING GUIDE CITY EXPRESS & EXPRESS



| RAMP MODEL | RAMP LENGTH (IN) | WEIGHT BASE UNIT (LBS) | WEIGHT CAPACITY (LBS) | STORED HEIGHT (IN) | BASEPLATE DEPTH (IN) | BASEPLATE WIDTH (IN) | SPRING ASSIST | LOAD WIDTH - RAMP LENGTH |        |        |        |        |
|------------|------------------|------------------------|-----------------------|--------------------|----------------------|----------------------|---------------|--------------------------|--------|--------|--------|--------|
|            |                  |                        |                       |                    |                      |                      |               | 24 IN.                   | 30 IN. | 36 IN. | 42 IN. | 51 IN. |

### CITY EXPRESS STANDARD ROOF

|      |    |         |       |      |       |               |  |  |       |       |  |  |
|------|----|---------|-------|------|-------|---------------|--|--|-------|-------|--|--|
| LB20 | 81 | 103-118 | 1,500 | 46.4 | 11.25 | 36.25 - 42.25 |  |  | 30-81 | 36-81 |  |  |
|------|----|---------|-------|------|-------|---------------|--|--|-------|-------|--|--|

### EXPRESS STANDARD ROOF

|      |     |         |       |      |       |               |      |        |        |        |  |  |
|------|-----|---------|-------|------|-------|---------------|------|--------|--------|--------|--|--|
| LB20 | 81  | 103-118 | 1,500 | 46.4 | 11.25 | 36.25 - 42.25 | Yes* |        | 30-81  | 36-81  |  |  |
| LB10 | 81  | 82-102  | 1,000 | 46.5 | 11    | 30.25 - 42.25 |      | 24-81  | 30-81  | 36-81  |  |  |
| LT30 | 119 | 110-140 | 1,000 | 46.5 | 15    | 30.25 - 42.25 |      | 24-119 | 30-119 | 36-119 |  |  |

**NOTE:** (\*) The 7842A207 (LB20-30-81) is not available with a spring assist.

**WARNING:** Link products must be professionally installed by a trained technician when being placed into an Electric Vehicle (EV). Electric Vehicles have higher voltage batteries and cables and drilling into Electric Vehicles may cause serious bodily harm and possibly death. Link is not responsible for optional configurations or equipment that restrict the installation of this product in any way. Consult OEM body builder guides for additional installation guidelines.