



RAMP MODEL	RAMP LENGTH (IN)	WEIGHT BASE UNIT (LBS)	WEIGHT CAPACITY (LBS)	STORED HEIGHT (IN)	BASEPLATE DEPTH (IN)	BASEPLATE WIDTH (IN)	LOAD ANGLE	SPRING ASSIST	LOAD WIDTH - RAMP LENGTH			
									24 IN.	30 IN.	36 IN.	42 IN.

CITY EXPRESS STANDARD ROOF

LB20	72	96	1,500	41.5	11.25	36.25	16			30-72		
LB20	81	103-118	1,500	46.4	11.25	36.25 - 42.25	14			30-81	36-81	

EXPRESS STANDARD ROOF

LB20	72	96	1,500	41.5	11.25	36.25	23			30-72		
LB20	81	103-118	1,500	46.4	11.25	36.25 - 42.25	20	*		30-81	36-81	
LB10	81	82-102	1,000	46.5	11	30.25 - 42.25	20			24-81	30-81	36-81
LT30	119	110-140	1,000	46.5	15	30.25 - 42.25	14			24-119	30-119	36-119

NOTE: (*) The 7842A208 (LB20-30-72) and 7842A207 (LB20-30-81) are not available with a spring assist.

WARNING: Link products must be professionally installed by a trained technician when being placed into an Electric Vehicle (EV). Electric Vehicles have higher voltage batteries and cables and drilling into Electric Vehicles may cause serious bodily harm and possibly death. Link is not responsible for optional configurations or equipment that restrict the installation of this product in any way. Consult OEM body builder guides for additional installation guidelines.