
# SPECIFICATIONS ORDER GUIDE SERVICE KITS AND PARTS

## **20K Auxiliary Suspension**



The Link 20K Auxiliary Suspension is a lightweight, 20,000 pound capacity, selfsteering lift axle that incorporates several unique features. The patented, interchangeable ride height brackets allow the installer to manage inventory dollars and still have a lift axle available for almost any truck. The improved lift spring geometry of the Link 20K Auxiliary Suspension assures longer life of the lift springs and less downtime for the owner. The compact mounting envelope (22.5") combined with the integrated air control system (optional) saves valuable frame rail space. The separate ride height brackets and pre-plumbed integrated air control kit can save up to 3-5 hours of installation time.

Link Mfg. Ltd. 223 15th St. N.E. Sioux Center, IA USA 51250-2120 www.linkmfg.com

SUD

QUESTIONS? CALL CUSTOMER SERVICE 1-800-222-6283

#### SUSPENSION-AXLE, UNITIZED (BASE UNIT)

- 8A000850 AUXILIARY SUSPENSION, 20K
- 8A000852 AUXILIARY SUSPENSION, 20K INTEGRATED AIR

#### FRAME BRACKET KITS, (CHOOSE ONE)

#### STANDARD FRAME BRACKETS

#### TALL FRAME BRACKETS

- 8A000424 8 10 1/2" RIDE HEIGHT
- 8A000420
   8 10 1/2" RIDE HEIGHT (NO SPACER)

   8A000421
   10 12 1/2" RIDE HEIGHT (2" SPACER)
- ── 8A000422 12 14 1/2" RIDE HEIGHT (4" SPACER)
- 8A000425 10 12 1/2" RIDE HEIGHT
- 8A000426 12 14 1/2" RIDE HEIGHT

#### AIR CONTROL KITS FOR INTEGRATED SUSPENSIONS (CHOOSE ONE)

13501023 CONTROL-INTEGRATED-STANDARD

13501024 CONTROL-INTEGRATED-SEALED

#### OPTIONAL AIR CONTROL KITS FOR NON-INTEGRATED SUSPENSION (CHOOSE ONE)

- 13501025 CONTROL-NON-INTEGRATED-STANDARD
- 13501026 CONTROL-NON-INTEGRATED-SEALED

#### **OPTIONAL KITS**

- B00A0032 FASTENER KIT 2" FASTENERS
- 800A0305 FASTENER KIT 2 1/2" FASTENERS"
- 13501016 RATIO RELAY VALVE KIT
- 13501029 KIT-AIR TANK

To order your Link 20K Auxiliary Suspension, use the order form on page 2 of this document to assist with your specific selections.

- 1. Order the Base Unit.
- 2. Order the Ride Height Bracket Kit.
  - a) Determine the Loaded Tire Radius on the chart.
  - b) Subtract Loaded Tire Radius from Loaded Frame Height to find correct ride height.
- Greyed out area of table not typically used for 20K applications

#### Loaded Frame Height - Loaded Tire Radius = Ride Height

- c) Select the correct Ride Height Bracket part number from the chart from page 5 or 6 depending on your application.
- 4. Choose the desired Air Control Kit.
- 5. Select any additional Optional Equipment.
- 6. Call your Link Manufacturing Sales representative at the number below to place your order.

### **QUICK SPECS**


MODEL: 20K


TYPE: SELF-STEER


WEIGHT: 1,300 LBS

- CAPACITY: 20,000 LBS
- TRAVEL: 12"
- LIFT: 7 9 1/2"
- **RIDE HEIGHT: 8 14 1/2"**
- ENVELOPE: 22 1/2"
- FRAME WIDTH: 33 3/8 35"

TUBE TYPE	TUBELESS	ISO (METRIC)	LOADED TIRE RADIUS	DIAMETER
8.25R20	9R22.5	255/80R22.5	18	38.4
		265/75R22.5	18	38.2
		295/70R22.5	18.2	38.7
9.00R20	10R22.5	295/75R22.5	18.5	40.2
		275/80R22.5	19	40.4
	11R22.5	295/80R22.5	19.5	41.9
10.00R20		445/65R19.5	19.5	42.6
		285/75R24.5	19.5	42.7
		315/80R22.5	19.9	42.8
		385/65R22.5	19.5	42.3
11.00R20		275/80R24.5	19.5	41.3
10.00R22	12R22.5		20	42.8
12.00R20	13R22.5	425/65R22.5	20.5	44.5
11.00R22	11R24.5		20.5	44
12.00R22	12R24.5	445/65R22.5	21	45
13.00R20			21.5	46
11.00R24	13R24.5		21.5	46.3
12.00R24			22	47.6









20K LIFT CHART	RIDE H	DE HEIGHT 305mm-368mm / 12.0in - 14.5in (FRAME MOUNT KIT 8A000422 OR 8A000426)												
LOADED FRAME HEIGHT	762mm 30.0in						838mm 33.0in						914mm 36.0in	927mm 36.5in
TIRE RADIUS														
18 (LOADED)	178mm 7.0in	191mm 7.5in	203mm 8.0in	216mm 8.5in	229mm 9.0in	241mm 9.5in								
19 (LOADED)			178mm 7.0in	191mm 7.5in	203mm 8.0in	216mm 8.5in	229mm 9.0in	241mm 9.5in						
20 (LOADED)					178mm 7.0in	191mm 7.5in	203mm 8.0in	216mm 8.5in	229mm 9.0in	241mm 9.5in				
21 (LOADED)							178mm 7.0in	191mm 7.5in	203mm 8.0in	216mm 8.5in	229mm 9.0in	241mm 9.5in		
22 (LOADED)									178mm 7.0in	191mm 7.5in	203mm 8.0in	216mm 8.5in	229mm 9.0in	241mm 9.5in


SERVICE ITEMS FOR 20K AUXILIARY SUSPENSION						
ITEM NUMBER	DESCRIPTION					
4AS00022	SERVICE KIT - STEERING STOP BOLT					
4AS00023	SERVICE KIT - COMPLETE STEERING STABILIZER					
4AS00043	SERVICE KIT - SLACK ADJUSTER					
4AS00053	SERVICE KIT - CAMSHAFT-LH					
4AS00054	SERVICE KIT - CAMSHAFT-RH					
4AS00055	SERVICE KIT - CHAMBER-BRAKE					
4AS00056	SERVICE KIT - ASSEMBLY-ROD, TIE					
4AS00057	SERVICE KIT - ASSEMBLY HANGER					
4AS00058	SERVICE ASSEMBLY - AXLE-FABRICATED					
4AS00059	SERVICE ASSEMBLY - KNUCKLE-MACHINED-LH					
4AS00060	SERVICE ASSEMBLY - KNUCKLE-MACHINED-RH					
4AS00061	SERVICE KIT - TIE ROD END (LH THREAD)					
4AS00062	SERVICE KIT - TIE ROD END (RH THREAD)					
4AS00063	SERVICE KIT - ASSEMBLY TUBE-TIE ROD					
4AS00064	SERVICE KIT - COMPLETE BUSHING					
4AS00065	SERVICE KIT - UPPER ARM-LH					
4AS00066	SERVICE KIT - UPPER ARM-RH					
4AS00067	SERVICE KIT - LOWER ARM-LH					
4AS00068	SERVICE KIT - LOWER ARM-RH					
4AS00069	SERVICE KIT - LIFT SPRING					
4AS00070	SERVICE KIT - LOAD SPRING					
4AS00071	SERVICE KIT - COMPLETE KINGPIN					
4AS00073	SERVICE KIT - COMPLETE CAM BUSHING AND SEAL					
4AS00074	SERVICE KIT - COMPLETE BRAKE					
4AS00080	SERVICE KIT - WHEEL NUT					
4AS00081	SERVICE KIT - BEARINGS AND SEALS					
4AS00082	SERVICE KIT - HUB CAP ASSEMBLY					
4AS00083	SERVICE KIT - NUT-PRO-TORQ. 1.75-12					
4AS00084	SERVICE KIT - COMPLETE RIDE SHOCK					





4AS00022 - SERVICE KIT - STEERING STOP BOLT					
ITEM	DESCRIPTION QTY				
1	5/8 UNC HEX JAM NUT, GR 5	1			
2	BOLT-STOP, STEERING, GEOMET	1			


4AS	4AS00023 - SERVICE KIT - COMPLETE STEERING STABILIZER						
ITEM	ITEM DESCRIPTION QT						
1	HEX HEAD FLANGE SCREW, M12 X 1.75 X 110, CLASS 10.9	2					
2	HEX HEAD FLANGE SCREW, M12 X 1.75 X 80, CLASS 10.9	2					
3	HEX TOP LOCK NUT, M12 X 1.75, 10	4					
4	SHOCK ABSORBER, WIDE BODY	2					
5	WASHER-HARDENED, 12MM	4					























	4AS00066 - SERVICE KIT - UPPER ARM-RH
	ITEM         DESCRIPTION         QTY           1         ARM ASSEMBLY-TRAILING, UPPER RH         1
	2 HEX CAP SCREW, M20 X 2.5 X 150, CLASS 10.9 2
	3 HEX TOP LOCK NUT, M20 X 2.5, 10 2
(2)	4 WASHER-HARDENED, 20MM 4
$\sim$	
	A
(4)	
00-	
	<b>A</b>
	S ) 1100
	$\mathbf{O}$
0	
( <b>1</b> )	
$\bigcirc$	
<b>(4) (1)</b>	4AS00067 - SERVICE KIT - LOWER ARM-LH
$\mathbf{\dot{\mathbf{Y}}}$	ITEM DESCRIPTION QTY
	1 ARM ASSEMBLY-TRAILING, LOWER LH 1
	2         HEX CAP SCREW, M20 X 2.5 X 150, CLASS 10.9         2           3         HEX TOP LOCK NUT, M20 X 2.5, 10         2
	4 WASHER-HARDENED, 20MM 4
	$\sim$
2	
	(3)



		(	3 1
			4AS00070 - SERVICE KIT - LOAD SPRING         ITEM       DESCRIPTION       QTY         1       HEX HEAD FLANGE SCREW, M10 X 1.50 X 20, CLASS 10.9       2         2       M12 X 1.75 HEX FLANGE NYLOCK NUT (CLASS 8)       2         3       METRIC FLAT HEAD CAP SCREW, M10 X 1.50, CLASS 10.9       2         4       SPRING-AIR       1
			4
		2	
4ASI ITEM	00071 - SERVICE KIT - COMPLETE KIN DESCRIPTION		
1 2	7/16 UNC TOP LOCK FL NUT (GR G) O&P BUSHING-KINGPIN	2 4	
3	CAP-KING PIN	4	
4	FITTING-GREASE	4	
5	KING PIN-20K	2	
6	PIN-DRAW, LOCKING	2	
7	RETAINER-THRUST BEARING, 20K	2	
8	SEAL-KNUCKLE SHIM (.005)	4	
10	SHIM (.005) SHIM (.015)	2	
10	SHIM (.013) SHIM (.030)	2	
11	THRUST BEARING-KNUCKLE, 20K	2	
	,,,,,,,		





INCLUDES OUTER BEARING RACE


4AS	4AS00081 - SERVICE KIT - BEARINGS AND SEALS				
ITEM	ITEM DESCRIPTION				
1	1 BEARING-CONE-INNER - 2.250 ID				
2	BEARING-INNER-CONE - 3.000 ID				
3	3 GASKET				
4 ROLLER BEARING, CUP		2			
5	SEAL-OIL	1			


Ð

Ø

C







4AS00084 - SERVICE KIT - COMPLETE RIDE SHOCK					
ITEM	DESCRIPTION	QTY			
1	HEX CAP SCREW, M16 X 2.0 X 110, 10.9	2			
2	HEX CAP SCREW, M16 X 2.0 X 90, 10.9	2			
3	HEX TOP LOCK FLANGE NUT, M16 X 2.0, CLASS 10	4			
4	SHOCK ABSORBER	2			
5	WASHER-OVERSIZED, 16MM	4			



LINK MANUFACTURING, LTD. 223 15TH ST. NE, SIOUX CENTER, IA 51250 1-800-222-6283 www.linkmfg.com