

Mounted Ramps

MODEL # (Style-W-L)	HEIGHT STORED (INCHES)	BASEPLATE DEPTH (INCHES)	BASEPLATE WIDTH (INCHES)
------------------------	------------------------------	--------------------------------	--------------------------------

LB10 Side Step Mount (Bifold Design)

LB10-24-81	44.75	15	30.25
LB10-30-81	44.75	15	36.25
LB10-30-90	48.75	15	36.25
LB10-36-81	44.75	15	42.25
LB10-36-90	48.75	15	42.25

LB20 Flat Mount (Bifold Design)

LB20-24-72	41.5	15	30.25
LB20-24-81	46.5	15	30.25
LB20-24-90	50.5	15	30.25
LB20-24-99	55.5	15	30.25
LB20-24-108	59.5	15	30.25
LB20-24-117	64.5	15	30.25
LB20-30-72	41.5	15	36.25
LB20-30-81	46.5	15	36.25
LB20-30-90	50.5	15	36.25
LB20-30-99	55.5	15	36.25
LB20-30-108	59.5	15	36.25
LB20-30-117	64.5	15	36.25
LB20-30-126	68.5	15	36.25
LB20-36-72	41.5	15	42.25
LB20-36-81	46.5	15	42.25
LB20-36-90	50.5	15	42.25
LB20-36-99	55.5	15	42.25
LB20-36-108	59.5	15	42.25
LB20-36-117	64.5	15	42.25
LB20-36-126	68.5	15	42.25
LB20-36-135	73.5	15	42.25
LB20-36-81*	46.5	15	42.25
LB20-36-90*	50.5	15	42.25
LB20-42-108	59.5	15	51
LB20-47-99	55.5	15	56

MODEL # (Style-W-L)	HEIGHT STORED (INCHES)	BASEPLATE DEPTH (INCHES)	BASEPLATE WIDTH (INCHES)
------------------------	------------------------------	--------------------------------	--------------------------------

LB10 Side Step Mount (Bifold Design)

LB10-24-81	44.75	15	30.25
LB10-30-81	44.75	15	36.25
LB10-30-90	48.75	15	36.25
LB10-36-81	44.75	15	42.25
LB10-36-90	48.75	15	42.25

LT30 Flat Mount (Trifold Design)

LT30-24-119	46.75	15	30.25
LT30-30-119	46.75	15	36.25
LT30-36-119	46.75	15	42.25

LSR90 Swivel Ramp (Bifold Design)

LSR90-30-99	58.75	49.75	38.5
LSR90-30-108	63	49.75	38.5
LSR90-30-117	67.75	49.75	38.5
LSR90-36-99	58.75	55.75	44.5
LSR90-36-108	63	55.75	44.5
LSR90-36-117	67.75	55.75	44.5
LSR90-47-99	58.75	66.75	55

*Note: All Folding Ramps collapse to roughly 7.5 inches wide

RAMP SPECIFICATIONS

Portable Ramps

MODEL # (Style-W-L)	FOLDED LENGTH (INCHES)	RAMP WIDTH + SIDERAILS (INCHES)	SIDERAIL HEIGHTS (INCHES)
------------------------	---------------------------	------------------------------------	------------------------------

LWS40 Lightweight (Bifold Design)

LWS40-24-72 F	42.25	25.5	1.65
LWS40-24-81 F	45.88	25.5	1.65
LWS40-24-90 F	51.25	25.5	1.65
LWS40-30-72 F	42.25	31.5	1.65
LWS40-30-90 F	51.25	31.5	1.65
LWS40-30-108 F	60.25	31.5	1.65
LWS40-36-99 F	54.88	37.5	1.65
LWS40-36-108 F	60.25	37.5	1.65

LS50 Heavy Duty (Bifold Design)

LS50-24-72 F	42.53	27.25	1.42
LS50-24-90 F	51.53	27.25	1.42
LS50-30-81 F	46.2	33.25	1.42
LS50-30-90 F	51.53	33.25	1.42
LS50-30-99 F	55.2	33.25	1.42
LS50-30-108 F	60.53	33.25	1.42
LS50-30-117 F	64.2	33.25	1.42
LS50-36-90 F	51.53	39.25	1.42
LS50-36-99 F	55.2	39.25	1.42
LS50-36-108 F	60.53	39.25	1.42

*Note: All Folding Ramps collapse to roughly 7.5 inches wide

LWS40 Straight Design

Ramp Width + Siderails 1 inch wider than usable width

Siderail Height 1.65 Inches

LS50 Straight Design

Ramp Width + Siderails 2 3/4 inches wider than usable width

Siderail Height 1.42 inches

Swivel Ramp Clearance

In the stowed position, the wheel on the pivot side of the ramp will need approximately a 7.5-inch radius of clearance from the pivot center to operate properly. The widest ramp at 47 inches will need approximately a 55-inch radius of clearance to operate properly.

It is recommended that the ramp be positioned and moved through the full 180 degrees of motion to ensure proper clearance before drilling holes. This activity requires two people.

